

## DECLARATION OF PERFORMANCE

N° 001-MG-ALU DoP

1. Unique identification code of the product-type:

### M&G System Chimneys with Aluminum flue liner

EN 1856-1: 2009

#### Aluminum sections, fittings, and terminals

<b>0.1</b>	(Dn 60-250*)	(rigid, single)	(flue)	<b>T200 P1</b>	<b>W</b>	<b>V1</b>	<b>L10/11/13 150</b>	<b>O30</b>
<b>0.2</b>	(Dn 60-150)	(rigid, single)	(flue)	<b>T250 P1</b>	<b>W</b>	<b>V1</b>	<b>L10/11/13 150</b>	<b>O40</b>
<b>0.4</b>	(Dn 60/100-130/200)	(rigid, conc.)	(flue/air)	<b>T200 P1</b>	<b>W</b>	<b>V1</b>	<b>L10/11/13 150</b>	<b>O00</b>
<b>0.4a</b>	(Dn 60/100-100/150, IA)	(rigid, conc.)	(flue/air)	<b>T200 P1</b>	<b>W</b>	<b>V1</b>	<b>L10/11/13 150</b>	<b>O00</b>
<b>0.5</b>	(Dn 60/100-130/200)	(rigid, conc.)	(flue/air)	<b>T250 P1</b>	<b>W</b>	<b>V1</b>	<b>L10/11/13 150</b>	<b>O00</b>
<b>0.6</b>	(Dn 70-150)	(rigid, single)	(flue)	<b>T250 P1</b>	<b>D</b>	<b>Vm</b>	<b>L11070</b>	<b>O40</b>
<b>0.7</b>	(Dn 70-200; NEN 7203)	(rigid, single)	(flue)	<b>T250 N1</b>	<b>D</b>	<b>Vm</b>	<b>L11045/063</b>	<b>O40</b>
<b>0.8</b>	(Dn 250-300)	(rigid, single)	(flue)	<b>T250 N1</b>	<b>D</b>	<b>Vm</b>	<b>L11045/063</b>	<b>O40</b>
<b>0.8a</b>	(Dn 350-400)	(rigid, single)	(flue)	<b>T250 N1</b>	<b>D</b>	<b>Vm</b>	<b>L11045/063</b>	<b>O60</b>
<b>T.1</b>	(Terminal Dn 60/100-100/150)	(roof, wall)	(flue/air)	<b>T120 P1</b>	<b>W</b>	<b>V1</b>	<b>L13 150</b>	<b>O00</b>
<b>T.2</b>	(Terminal Dn 80-80)	(roof)	(flue/air)	<b>T120 P1</b>	<b>W</b>	<b>V1</b>	<b>L13 150</b>	<b>O30</b>
<b>A.1</b>	(Dn 60/100-100/150)	(rigid, conc.)	(flue/air)	<b>T200 P1</b>	<b>W</b>	<b>V1</b>	<b>L13 150</b>	<b>O00</b>

\*Only several parts, no complete system

Plus manufacturer's batch or date code: see product marking

2. Intended use/es:

Products for the construction of single wall or concentric system chimneys to convey the products of combustion from heating appliances to the outside atmosphere. Systems 0.4, 0.4a, 0.5, T.1, T.2 and A.1 are also suitable to supply combustion air from the outside.

3. Manufacturer:

M&G Group  
Burg. Grollemanweg 14  
9405 TN Assen  
The Netherlands  
E: info@mg-group.com

M&G-Italie S.P.A.  
Via Campagnola 6  
36040 Orgiano (VI)  
Italy  
E: info@mg-group.com

Ant Kalip  
Birlik Organize Sanayi Bölgesi Tem Yanyol  
1.Cadde No:29 Posta K34953  
Tuzla - Istanbul Turkey  
E: info@mg-group.com

4. Authorized representative:

Not applicable.

5. System/s AVCP:

System 2+.

6. Harmonized standard:

The approved body with No. 0120 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

7. Declared performance

	Essential Characteristics	Performance	Harmonized technical specification
1	<b>Compressive strength</b>		EN 1856-1:2009
	System 0.1, 0.2, 0.4, 0.5, 0.6, 0.7, 0.8 and 0.8a	Maximum height 24 m when using a support bend, unlimited if wall brackets are used every 2 m.	
	System 0.4a	Maximum height 10 m.	
	System T.1, T.2	Not applicable.	
	System A.1	Maximum 2 m.	
2	<b>Resistance to fire (tested fully enclosed with ventilated gap if applicable)</b>		
	System 0.1	T200 O30	
	System 0.2, 0.6, 0.7 and 0.8	T250 O40	
	System 0.8a	T250 O60	
	System 0.4, 0.4a and A.1	T200 O00	
	System 0.5	T250 O00	
	System T.1	T120 O00	
	System T.2	T120 O30	
3	<b>Gas tightness</b>		
	System 0.1, 0.2, 0.4, 0.4a, 0.5, 0.6, T1, T.2 and A.1	P1	
	System 0.7, 0.8 and 0.8a	N1	
4	<b>Flow resistance</b>	Flow resistances acc. to EN 13384-1, see datasheet.	
5	<b>Thermal resistance</b>	0.00 m <sup>2</sup> K/W	
6	<b>Thermal shock resistance</b>	No	
7	<b>Flexural tensile strength</b>		
	Non-vertical installation		
	Systems 0.1, 0.2, 0.4, 0.4a, 0.5, 0.6, 0.7, 0.8 and 0.8a	The maximum deflection is 87°. The maximum length of the horizontal part is not limited. One wall bracket should be used per chimney section and every 2 m.	
	System T.1, T.2	For vertical (roof) terminals: not applicable, wall terminals, see instructions.	
	System A.1	Not applicable, only for vertical installation.	
	Wind load for external installation		
	System 0.4, 0.5, T1, T.2 and terminal accessories of system 0.7	Unlimited, brackets should be used per chimney section, see instructions. Free height above last bracket 2 m.	
	System 0.4a	Unlimited, brackets should be used per chimney section, see instructions. Free height above last bracket 1 m.	
	System 0.1, 0.2, 0.6, 0.7, 0.8 and 0.8a	Not applicable, only indoor application.	
	System A.1	Only in combination with corresponding metal outer wall. Maximum height 2 m, use guy-wires for lengths above 1 m.	
8	<b>Resistance against condensation, water vapor diffusion and condensate penetration</b>		
	System 0.1, 0.2, 0.4, 0.4a, 0.5, T.1, T.2 and A.1	Yes	
	System 0.6, 0.7, 0.8 and 0.8a	No	
9	<b>Durability against corrosion</b>		
	System 0.1, 0.2, 0.4, 0.4a, 0.5, T.1, T.2 and A.1	V1	
	System 0.6, 0.7, 0.8 and 0.8a	Vm	
10	<b>Durability against rainwater</b>		
	System 0.4, 0.5, T.1, T.2 and A.1	Yes, system 0.4 and 0.5 only with additional sealant, see instructions. System A.1 only with corresponding metal outer wall.	
	System 0.1, 0.2, 0.4a, 0.6, 0.7, 0.8 and 0.8a	No, only indoor application.	
11	<b>Freeze-thaw resistance</b>	Yes	
12	<b>Dangerous substances</b>	Does not contain dangerous substances.	Relevant national regulations

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Gezienus Hoving | Plant Director

Assen (NL), 1 May 2024

001 MG-ALU-DoP V05.24